


Item no. DD130-1215WW9027-DM1

Series Name: Hospitality Antiglare  
downlight (DD130)



■ Direct Horizontal Illuminance DD130-1215WW9027-DM1

| φ    | Illuminance Angle | Beam Angle | Vertical Illuminance (lx) |
|------|-------------------|------------|---------------------------|
| 17°  | 17°               | 17°        | 22040                     |
| 290  | 1                 | 10000      | 5510                      |
|      |                   | 5000       | 2450                      |
| 590  | 2                 | 2000       | 1380                      |
|      |                   | 1000       | 880                       |
| 890  | 3                 | 500        | 610                       |
|      |                   |            | 450                       |
| 1190 | m                 | 1          | 340                       |

|                  |                         |                                |
|------------------|-------------------------|--------------------------------|
| Installation     | Recessed mount          |                                |
| Type             | Hospitality             | Antiglare<br>downlight (DD130) |
| Fixture wattage  | 12.1W                   |                                |
| Beam angle       | 17 deg                  |                                |
| Color Temp.      | 2700K                   |                                |
| CRI              | Ra>90                   |                                |
| Luminous         | 626 lm                  |                                |
| Body             | Die-cast aluminum alloy |                                |
| Body finish      | N/A                     |                                |
| Trim finish      | White                   |                                |
| Reflector finish | White                   |                                |
| IP Rate          | IP20                    |                                |
| Light source     | COB module              |                                |
| Input Voltage    | AC220~240V              |                                |
| Dimming Type     | 1-10v Dimmable          |                                |
| Certificate      | CE, CCC                 |                                |
| Cut Hole         | 60                      |                                |

