






Item no. DD098-4550MB9040D

Series Name: Φ150 Spark (Deep Cone)



|                  |                         |
|------------------|-------------------------|
| Installation     | Recessed mount          |
| Type             | Φ150 Spark (Deep Cone)  |
| Fixture wattage  | 44.3W                   |
| Beam angle       | 50 deg                  |
| Color Temp.      | 4000K                   |
| CRI              | Ra>90                   |
| Luminous         | 4074 lm                 |
| Body             | Die-cast aluminum alloy |
| Body finish      | N/A                     |
| Trim finish      | Black                   |
| Reflector finish | Mirror                  |
| IP Rate          | IP20                    |
| Light source     | COB module              |
| Input Voltage    | AC220~240V              |
| Dimming Type     | Non-Dimmable            |
| Certificate      | CE, CCC                 |
| Cut Hole         | 150mm                   |



| Height (Weight) | Spot / Medium / Medium flood | Wide flood  |
|-----------------|------------------------------|-------------|
| 65.3W           | 177 (1.4kg)                  |             |
| 48.5W           | 177 (1.5kg)                  |             |
| 44.3W           | 157 (1.2kg)                  |             |
| 33.8W           | 168 (1.1kg)                  | 157 (1.1kg) |
| 30.3W           | 168 (1.1kg)                  | 157 (1.1kg) |
| 23.0W           | 138 (0.9kg)                  | 127 (0.9kg) |