


Item no. DD053-1315MW9035

Series Name:  $\Phi$ 80 Series Reflector Type, Adjustable



■ Direct Horizontal Illuminance DD053-1315MW9035

| φ   | Illuminance Angle | Beam Angle | Vertical Illuminance (lx) |
|-----|-------------------|------------|---------------------------|
|     | 13°               | 13°        | 22830                     |
| 220 | 10000             |            | 5710                      |
|     | 5000              |            | 2540                      |
| 450 | 2000              |            | 1430                      |
|     | 1000              |            | 910                       |
| 680 | 500               |            | 630                       |
|     | 250               |            | 470                       |
| 910 | 125               |            | 360                       |

|                  |   |
|------------------|---|
| Installation     | Recessed mount                              |
| Type             | $\Phi$ 80 Series Reflector Type, Adjustable |
| Fixture wattage  | 12W   |
| Beam angle       | 15 deg                                      |
| Color Temp.      | 3500K                                       |
| CRI              | Ra>90                                       |
| Luminous         | 565 lm                                      |
| Body             | Die-cast aluminum alloy                     |
| Body finish      | N/A   |
| Trim finish      | White                                       |
| Reflector finish | Mirror                                      |
| IP Rate          | IP20  |
| Light source     | COB module                                  |
| Input Voltage    | AC220~240V                                  |
| Dimming Type     | Non-Dimmable                                |
| Certificate      | CE, CCC                                     |
| Cut Hole         | 80mm  |

