


Item no. DD099-2515MW8530

Series Name:  $\Phi$ 125 Spark



|                  |                         |
|------------------|-------------------------|
| Installation     | Recessed mount          |
| Type             | $\Phi$ 125 Spark        |
| Fixture wattage  | 23W                     |
| Beam angle       | 18 deg                  |
| Color Temp.      | 3000K                   |
| CRI              | Ra>85                   |
| Luminous         | 2194 lm                 |
| Body             | Die-cast aluminum alloy |
| Body finish      | N/A                     |
| Trim finish      | White                   |
| Reflector finish | Mirror                  |
| IP Rate          | IP20                    |
| Light source     | COB module              |
| Input Voltage    | AC220~240V              |
| Dimming Type     | Non-Dimmable            |
| Certificate      | CE, CCC                 |
| Cut Hole         | 125mm                   |



■ Direct Horizontal Illuminance DD099-2515MW8530

| φ    | Illuminance Angle | Beam Angle | Vertical Illuminance (lx) |
|------|-------------------|------------|---------------------------|
| 310  | 18°               | 18°        | 52430                     |
| 1    |                   |            | 13110                     |
| 630  |                   |            | 5830                      |
| 2    |                   |            | 3280                      |
| 950  |                   |            | 2100                      |
| 3    |                   |            | 1460                      |
| 1260 |                   |            | 1070                      |
| m    | 1                 | 0          | 820                       |

