


Item no. DD099-3015WW8527D

Series Name:  $\Phi$ 125 Spark (Deep Cone)



■ Direct Horizontal Illuminance DD099-3015WW8527D

| φ    | Illuminance Angle | Beam Angle | Vertical Illuminance (lx) |
|------|-------------------|------------|---------------------------|
| 290  | 17°               | 17°        | 63690                     |
| 1    |                   |            | 15920                     |
|      |                   |            | 7080                      |
| 590  |                   |            | 3980                      |
| 2    |                   |            | 2550                      |
| 890  |                   |            | 1770                      |
| 3    |                   |            | 1300                      |
| 1190 |                   |            | 1000                      |

|                  |                              |
|------------------|------------------------------|
| Installation     | Recessed mount               |
| Type             | $\Phi$ 125 Spark (Deep Cone) |
| Fixture wattage  | 30.3W                        |
| Beam angle       | 17 deg                       |
| Color Temp.      | 2700K                        |
| CRI              | Ra>85                        |
| Luminous         | 2548 lm                      |
| Body             | Die-cast aluminum alloy      |
| Body finish      | N/A                          |
| Trim finish      | White                        |
| Reflector finish | White                        |
| IP Rate          | IP20                         |
| Light source     | COB module                   |
| Input Voltage    | AC220~240V                   |
| Dimming Type     | Non-Dimmable                 |
| Certificate      | CE, CCC                      |
| Cut Hole         | 125mm                        |

