


Item no. DD099-3015WW8535D

Series Name:  $\Phi$ 125 Spark (Deep Cone)



■ Direct Horizontal Illuminance DD099-3015WW8535D

| φ    | Illuminance Angle | Beam Angle | Vertical Illuminance (lx) |   |      |
|------|-------------------|------------|---------------------------|---|------|
| 290  | 17°               | 17°        | 67670                     |   |      |
| 1    |                   |            | 16920                     |   |      |
| 590  |                   |            | 7520                      |   |      |
| 2    |                   |            | 4230                      |   |      |
| 890  |                   |            | 2710                      |   |      |
| 3    |                   |            | 1880                      |   |      |
| 1190 |                   |            | 1380                      |   |      |
| m    | 1                 | 0          | 1                         | 2 | 1060 |

|                  |                              |
|------------------|------------------------------|
| Installation     | Recessed mount               |
| Type             | $\Phi$ 125 Spark (Deep Cone) |
| Fixture wattage  | 30.3W                        |
| Beam angle       | 17 deg                       |
| Color Temp.      | 3500K                        |
| CRI              | Ra>85                        |
| Luminous         | 2707 lm                      |
| Body             | Die-cast aluminum alloy      |
| Body finish      | N/A                          |
| Trim finish      | White                        |
| Reflector finish | White                        |
| IP Rate          | IP20                         |
| Light source     | COB module                   |
| Input Voltage    | AC220~240V                   |
| Dimming Type     | Non-Dimmable                 |
| Certificate      | CE, CCC                      |
| Cut Hole         | 125mm                        |

