


Item no. DD100-1915DB8535D

Series Name: Φ 100 Spark (Deep Cone)



With Dark Mirror Reflector



■ Direct Horizontal Illuminance DD100-1915DB8535D

| φ | Illuminance Angle | Beam Angle | Vertical Illuminance (lx) | | |
|------|-------------------|------------|---------------------------|---|-----|
| 310 | 18° | 18° | 40640 | | |
| 1 | | | 10160 | | |
| 630 | | | 4520 | | |
| 2 | | | 2540 | | |
| 950 | | | 1630 | | |
| 3 | | | 1130 | | |
| 1260 | | | 830 | | |
| m | 1 | 0 | 1 | 2 | 640 |

| | |
|------------------|------------------------------|
| Installation | Recessed mount |
| Type | Φ 100 Spark (Deep Cone) |
| Fixture wattage | 18.6W |
| Beam angle | 18 deg |
| Color Temp. | 3500K |
| CRI | Ra>85 |
| Luminous | 1636 lm |
| Body | Dia-cast aluminum |
| Body finish | N/A |
| Trim finish | Black |
| Reflector finish | Dark Mirror |
| IP Rate | IP20 |
| Light source | COB module |
| Input Voltage | AC220~240V |
| Dimming Type | Non-Dimmable |
| Certificate | CE, CCC |
| Cut Hole | 100mm |

