


Item no. DD130-0515BB9030-DM1

Series Name: Hospitality Antiglare  
downlight (DD130)



■ Direct Horizontal Illuminance DD130-0515BB9030-DM1

| φ    | Illuminance Angle | Beam Angle | Vertical Illuminance (lx) |
|------|-------------------|------------|---------------------------|
| 17°  | 17°               | 17°        | 14440                     |
| 290  | 1                 | 5000       | 3610                      |
| 590  | 2                 | 2000       | 1600                      |
| 890  | 3                 | 1000       | 900                       |
| 1190 | m                 | 500        | 580                       |
|      |                   |            | 400                       |
|      |                   |            | 290                       |
|      |                   |            | 230                       |

|                  |                         |                                |
|------------------|-------------------------|--------------------------------|
| Installation     | Recessed mount          |                                |
| Type             | Hospitality             | Antiglare<br>downlight (DD130) |
| Fixture wattage  | 7.2W                    |                                |
| Beam angle       | 17 deg                  |                                |
| Color Temp.      | 3000K                   |                                |
| CRI              | Ra>90                   |                                |
| Luminous         | 426 lm                  |                                |
| Body             | Die-cast aluminum alloy |                                |
| Body finish      | N/A                     |                                |
| Trim finish      | Black                   |                                |
| Reflector finish | Black                   |                                |
| IP Rate          | IP20                    |                                |
| Light source     | COB module              |                                |
| Input Voltage    | AC220~240V              |                                |
| Dimming Type     | 1-10v Dimmable          |                                |
| Certificate      | CE, CCC                 |                                |
| Cut Hole         | 60                      |                                |

