


Item no. DD098-3415DW9030D

Series Name:  $\Phi$ 150 Spark (Deep Cone)



White Reflector




■ Direct Horizontal Illuminance DD098-3415DW9030D

Illuminance Angle	Beam Angle	Vertical Illuminance (lx)
14°	1	93430
	2	23360
15°	1	10380
	2	5840
30°	1	3740
	2	2600
45°	1	1910
	2	1460

Luminous flux : 2775 lm

Installation	Recessed mount
Type	$\Phi$ 150 Spark (Deep Cone)
Fixture wattage	33.8W
Beam angle	15 deg
Color Temp.	3000K
CRI	Ra>90
Luminous	2777 lm
Body	Die-cast aluminum alloy
Body finish	N/A
Trim finish	White
Reflector finish	White
IP Rate	IP20
Light source	COB module
Input Voltage	AC220~240V
Dimming Type	Non-Dimmable
Certificate	CE, CCC
Cut Hole	150mm



Height (Weight)	Spot / Medium / Medium flood	Wide flood
65.3W	177 (1.4kg)	
48.5W	177 (1.5kg)	
44.3W	157 (1.2kg)	
33.8W	168 (1.1kg)	157 (1.1kg)
30.3W	168 (1.1kg)	157 (1.1kg)
23.0W	138 (0.9kg)	127 (0.9kg)

