


Item no. SD382-2015W9035-R-IK

Series Name: Cylinder Arm Reflector in-track tracklight.(SD382-R-IK)



■ Direct Horizontal Illuminance SD382-2015W9035-R-IK

| φ   | Illuminance Angle | Beam Angle | Vertical Illuminance (lx) |
|-----|-------------------|------------|---------------------------|
| 240 | 14°               | 15°        | 51660                     |
| 1   |                   |            | 12910                     |
|     |                   |            | 5740                      |
| 480 |                   |            | 3230                      |
| 2   |                   |            | 2070                      |
| 730 |                   |            | 1430                      |
| 3   |                   |            | 1050                      |
| 980 |                   |            | 810                       |

|                  |                                                         |
|------------------|---------------------------------------------------------|
| Installation     | Track mount                                             |
| Type             | Cylinder Arm Reflector in-track tracklight.(SD382-R-IK) |
| Fixture wattage  | 21W                                                     |
| Beam angle       | 15 deg                                                  |
| Color Temp.      | 3500K                                                   |
| CRI              | Ra>90                                                   |
| Luminous         | 2036 lm                                                 |
| Body             | Die-cast aluminum alloy                                 |
| Body finish      | White                                                   |
| Trim finish      | N/A                                                     |
| Reflector finish | N/A                                                     |
| IP Rate          | IP20                                                    |
| Light source     | COB module                                              |
| Input Voltage    | AC220~240V                                              |
| Dimming Type     | Non-Dimmable                                            |
| Certificate      | CE,CCC                                                  |
| Cut Hole         | N/A                                                     |

