


Item no. DD136-2815W9040-R

Series Name: Versa R-G (DD136-R)



■ Direct Horizontal Illuminance DD136-2815W9040-R

| φ   | Illuminance Angle | Beam Angle | Vertical Illuminance (lx) |   |      |
|-----|-------------------|------------|---------------------------|---|------|
| 190 | 11°               | 12°        | 123990                    |   |      |
| 1   |                   |            | 31000                     |   |      |
| 380 |                   |            | 13780                     |   |      |
| 2   |                   |            | 7750                      |   |      |
| 570 |                   |            | 4960                      |   |      |
| 3   |                   |            | 3440                      |   |      |
| 770 |                   |            | 2530                      |   |      |
| m   | 1                 | 0          | 1                         | 2 | 1940 |

|                  |                         |
|------------------|-------------------------|
| Installation     | Recessed mount          |
| Type             | Versa R-G (DD136-R)     |
| Fixture wattage  | 28W                     |
| Beam angle       | 12 deg                  |
| Color Temp.      | 4000K                   |
| CRI              | Ra>90                   |
| Luminous         | 3203 lm                 |
| Body             | Die-cast aluminum alloy |
| Body finish      | N/A                     |
| Trim finish      | White                   |
| Reflector finish | N/A                     |
| IP Rate          | IP20                    |
| Light source     | COB module              |
| Input Voltage    | AC220~240V              |
| Dimming Type     | Non-Dimmable            |
| Certificate      | CE, CCC                 |
| Cut Hole         | 150mm                   |

