


Item no. SD359-2515B9040-IK

Series Name: Lens type Cylinder
Tracklight (In Tack) (SD359-IK)



■ Lighting Distribution Curve (cd/1000 lm)



■ Direct Horizontal Illuminance SD359-2515B9040-IK

| φ | Illuminance Angle | Beam Angle | Vertical Illuminance(lx) |
|---|-------------------|------------|--------------------------|
| 1 | 17° | 17° | 74080 |
| 2 | | | 18520 |
| 3 | | | 8230 |
| 4 | | | 4630 |
| 5 | | | 2960 |
| 6 | | | 2060 |
| 7 | | | 1510 |
| 8 | | | 1160 |

Luminous flux : 2245 lm

| | |
|------------------|-------------------------|
| Installation | Track mount |
| Type | |
| Fixture wattage | 24.3W |
| Beam angle | 17 |
| Color Temp. | 4000K |
| CRI | Ra>90 |
| Luminous | 2247 lm |
| Body | Die-cast aluminum alloy |
| Body finish | Black |
| Trim finish | Black |
| Reflector finish | N/A |
| IP Rate | IP20 |
| Light source | COB module |
| Input Voltage | AC220~240V |
| Dimming Type | Non-Dimmable |
| Certificate | CE,CCC |
| Cut Hole | N/A |

