


Item no. SD379-1515B9027S

Series Name: AMMA Lens type Cylinder Tracklight (SD379)



■ Lighting Distribution Curve (cd/1000 lm)



■ Direct Horizontal Illuminance SD379-1515B9027S

| φ | Illuminance Angle | Beam Angle | Vertical Illuminance(lx) |
|------|-------------------|------------|--------------------------|
| 1 | 15° | 16° | 45240 |
| 260 | | | 11310 |
| 1 | | | 5030 |
| 2 | | | 2830 |
| 520 | | | 1810 |
| 3 | | | 1260 |
| 780 | | | 920 |
| 1050 | | | 710 |
| m | | | |
| | | | Luminous flux : 1295 lm |

| | |
|------------------|--|
| Installation | Track mount |
| Type | AMMA Lens type Cylinder Tracklight (SD379) |
| Fixture wattage | 14W |
| Beam angle | 16deg |
| Color Temp. | 2700K |
| CRI | Ra>90 |
| Luminous | 1295 lm |
| Body | Die-castaluminumalloy |
| Body finish | Black |
| Trim finish | Black |
| Reflector finish | N/A |
| IP Rate | IP20 |
| Light source | COB module |
| Input Voltage | AC220~240V |
| Dimming Type | Non-Dimmable |
| Certificate | CE,CCC |
| Cut Hole | N/A |

