


Item no. DD133-0515B9040

Series Name:  $\Phi$ 80 series (DD133)



|                  |                                      |
|------------------|--------------------------------------|
| Installation     | Recessed mount                       |
| Type             | Lens type small adjustable downlight |
| Fixture wattage  | 5W                                   |
| Beam angle       | 16deg                                |
| Color Temp.      | 4000K                                |
| CRI              | Ra>90                                |
| Luminous         | 435 lm                               |
| Body             | Die-cast aluminum alloy              |
| Body finish      | N/A                                  |
| Trim finish      | Black                                |
| Reflector finish | N/A                                  |
| IP Rate          | IP20                                 |
| Light source     | COB module                           |
| Input Voltage    | AC220~240V                           |
| Dimming Type     | Non-Dimmable                         |
| Certificate      | CE,CCC                               |
| Cut Hole         | 80mm                                 |

■ Lighting Distribution Curve (cd/1000 lm)



■ Direct Horizontal Illuminance DD133-0515B9040

| φ | Illuminance Angle | Beam Angle | Vertical Illuminance (lx) |
|---|-------------------|------------|---------------------------|
| 1 | 15°               | 16°        | 11670                     |
| 2 |                   |            | 2920                      |
| 3 |                   |            | 1300                      |
| 4 |                   |            | 730                       |
| 5 |                   |            | 470                       |
| 6 |                   |            | 320                       |
| 7 |                   |            | 240                       |
| 8 |                   |            | 180                       |

Luminous flux : 435 lm

