


Item no. DD146-2015W9030

Series Name: Cledy versa L-G (DD146)



■ Lighting Distribution Curve (cd/1000 lm)



■ Direct Horizontal Illuminance DD146-2015W9030

| φ   | Illuminance Angle | Beam Angle | Vertical Illuminance(lx) |
|-----|-------------------|------------|--------------------------|
| 12° | 12°               | 12°        | 149250                   |
| 210 | 1                 | 50000      | 37310                    |
| 420 | 2                 | 20000      | 16580                    |
| 630 | 3                 | 10000      | 9330                     |
| 840 | m                 | 0          | 5970                     |
|     |                   | 1          | 4150                     |
|     |                   | 2          | 3050                     |
|     |                   |            | 2330                     |

Luminous flux : 2515 lm

|                  |  |
|------------------|--|
| Installation     | Recessed mount                                 |
| Type             | High-efficiency Lens type adjustable downlight |
| Fixture wattage  | 21W  |
| Beam angle       | 12deg  |
| Color Temp.      | 3000K  |
| CRI              | Ra>90  |
| Luminous         | 2515 lm  |
| Body             | Die-castaluminumalloy                          |
| Body finish      | N/A  |
| Trim finish      | White  |
| Reflector finish | N/A  |
| IP Rate          | IP20   |
| Light source     | COB module                                     |
| Input Voltage    | AC220~240V                                     |
| Dimming Type     | Non-Dimmable                                   |
| Certificate      | CE,CCC   |
| Cut Hole         | 125mm  |

