


Item no. DD146-1515W9035

Series Name: Cledy versa L-G (DD146)



■ Lighting Distribution Curve (cd/1000 lm)



■ Direct Horizontal Illuminance DD146-1515W9035

| φ | Illuminance Angle | Beam Angle | Vertical Illuminance(lx) |
|-----|-------------------|------------|--------------------------|
| 220 | 13° | 14° | 63220 |
| 1 | | | 15810 |
| 2 | | | 7020 |
| 450 | | | 3950 |
| 2 | | | 2530 |
| 680 | | | 1760 |
| 3 | | | 1290 |
| 910 | | | 990 |

Luminous flux : 1230 lm

| | |
|------------------|--|
| Installation | Recessed mount |
| Type | High-efficiency Lens type adjustable downlight |
| Fixture wattage | 14W |
| Beam angle | 14deg |
| Color Temp. | 3500K |
| CRI | Ra>90 |
| Luminous | 1230 lm |
| Body | Die-castaluminumalloy |
| Body finish | N/A |
| Trim finish | White |
| Reflector finish | N/A |
| IP Rate | IP20 |
| Light source | COB module |
| Input Voltage | AC220~240V |
| Dimming Type | Non-Dimmable |
| Certificate | CE,CCC |
| Cut Hole | 100mm |

