


Item no. DD138-5020MB9035L


Series Name: Cledy spark (Shallow cone)
(DD138L)



■ Direct Horizontal Illuminance DD138-5020MB9035L

| Beam Angle | Vertical Illuminance (lx) |
|------------|---------------------------|
| 21° | 69010 |
| | 17250 |
| | 7670 |
| 22° | 4310 |
| | 2760 |
| | 1920 |
| | 1410 |
| | 1080 |

| | | |
|------------------|-------------------------|-------|
| Installation | Recessed mount | |
| Type | High-efficiency | Fixed |
| | downlight Φ 150 | |
| Fixture wattage | 48.5W | |
| Beam angle | 22deg | |
| Color Temp. | 3500K | |
| CRI | Ra>90 | |
| Luminous | 7037 lm | |
| Body | Die-cast aluminum alloy | |
| Body finish | N/A | |
| Trim finish | Black | |
| Reflector finish | Mirror | |
| IP Rate | IP20 | |
| Light source | COB module | |
| Input Voltage | AC220~240V | |
| Dimming Type | Non-Dimmable | |
| Certificate | CE,CCC | |
| Cut Hole | 150 | |



| Height (Weight) | |
|-----------------|-------------|
| 48.5W | 125 (1.4kg) |
| 41.0W | 106 (1.2kg) |
| 28.0W | 106 (1.2kg) |
| 23.0W | 76 (0.9kg) |
| 20.0W | 76 (0.9kg) |

