


Item no. DD138-2830MB9027D





Series Name: Cledy spark (Deep cone)
(DD138D)



■ Direct Horizontal Illuminance DD138-2830MB9027D

φ	Illuminance Angle	Beam Angle	Vertical Illuminance (lx)
460	26°	28°	44600
1			11150
920			4960
2			2790
1380			1780
3			1240
1840			910
m			700

Installation	Recessed Mount	
Type	High-efficiency downlight Φ150	Fixed
Fixture wattage	28W	
Beam angle	28 deg	
Color Temp.	2700K	
CRI	Ra>90	
Luminous	3125 lm	
Body	Die-castaluminumalloy	
Body finish	Black	
Trim finish	Black	
Reflector finish	Mirror	
IP Rate	IP20	
Light source	COB module	
Input Voltage	AC220~240V	
Dimming Type	Non-Dimmable	
Certificate	CE,CCC	
Cut Hole	150	



Height (Weight)	Spot / Medium / Medium flood	Wide flood
46.5W	175 (1.4kg)	
41.0W	155 (1.1kg)	
28.0W	166 (1.1kg)	155 (1.1kg)
23.0W	136 (0.9kg)	125 (0.9kg)
20.0W	136 (0.9kg)	125 (0.9kg)