


Item no. DD139-2015MB9027

Series Name: Cledy spark (Normal cone)
(DD139)



■ Lighting Distribution Curve (cd/1000 lm)



■ Direct Horizontal Illuminance DD139-2015MB9027

| φ | Illuminance Angle | Beam Angle | Vertical Illuminance(lx) |
|-----|-------------------|------------|--------------------------|
| 14° | 16° | | 53520 |
| 240 | 20000 | | 13380 |
| | 10000 | | 5950 |
| 480 | 5000 | | 3340 |
| | 2000 | | 2140 |
| 730 | | | 1490 |
| | | | 1090 |
| 980 | | | 840 |

Luminous flux : 2130 lm

| | |
|------------------|-------------------------|
| Installation | Recessed mount |
| Type | Fixed downlight Φ125 |
| Fixture wattage | 21W |
| Beam angle | 16 |
| Color Temp. | 2700K |
| CRI | Ra>90 |
| Luminous | 2129 lm |
| Body | Die-cast aluminum alloy |
| Body finish | N/A |
| Trim finish | Black |
| Reflector finish | Mirror |
| IP Rate | IP20 |
| Light source | COB module |
| Input Voltage | AC220~240V |
| Dimming Type | Non-Dimmable |
| Certificate | CE,CCC |
| Cut Hole | 125mm |

