


Item no. DD155-1010MB9035

Series Name: AMMA High-efficiency Lens type Antiglare downlight (DD155-AG)



■ Lighting Distribution Curve (cd/1000 lm)



■ Direct Horizontal Illuminance DD155-1010MB9035

| φ | Illuminance Angle | Beam Angle | Vertical Illuminance(lx) |
|-----|-------------------|------------|--------------------------|
| 190 | 11° | 12° | 63250 |
| 1 | | | 15810 |
| | | | 20000 |
| | | | 10000 |
| 380 | | | 5000 |
| 2 | | | 3950 |
| | | | 2530 |
| 570 | | | 1760 |
| 3 | | | 1290 |
| | | | 990 |
| 770 | | | |

Luminous flux : 910 lm

| | |
|------------------|---|
| Installation | Recessed mount |
| Type | Φ100 Lens type downlight : Antiglare type |
| Fixture wattage | 10.5W |
| Beam angle | 12deg |
| Color Temp. | 3500K |
| CRI | Ra>90 |
| Luminous | 910 lm |
| Body | Die-castaluminumalloy |
| Body finish | N/A |
| Trim finish | Black |
| Reflector finish | Mirror |
| IP Rate | IP20 |
| Light source | COB module |
| Input Voltage | AC220~240V |
| Dimming Type | Non-Dimmable |
| Certificate | CE,CCC |
| Cut Hole | 100mm |

