


Item no. SD381-2015W9030-R

Series Name: Cledy versa R-G (UL track)  
(SD381-R)



■ Direct Horizontal Illuminance SD381-2015W9030-R

| φ   | Illuminance Angle | Beam Angle | Vertical Illuminance (lx) |   |      |
|-----|-------------------|------------|---------------------------|---|------|
| 170 | 10°               | 11°        | 86700                     |   |      |
| 1   |                   |            | 21680                     |   |      |
| 340 | 20000             |            | 9630                      |   |      |
| 2   | 10000             |            | 5420                      |   |      |
| 520 | 5000              |            | 3470                      |   |      |
| 3   |                   |            | 2410                      |   |      |
| 690 | 2000              |            | 1770                      |   |      |
| m   | 1                 | 0          | 1                         | 2 | 1350 |

|                  |                       |                            |
|------------------|-----------------------|----------------------------|
| Installation     | Track mount           |                            |
| Type             | Extra                 | high-efficiency tracklight |
| Fixture wattage  | 20W                   |                            |
| Beam angle       | 11deg                 |                            |
| Color Temp.      | 3000K                 |                            |
| CRI              | Ra>90                 |                            |
| Luminous         | 2001 lm               |                            |
| Body             | Die-castaluminumalloy |                            |
| Body finish      | White                 |                            |
| Trim finish      | White                 |                            |
| Reflector finish | N/A                   |                            |
| IP Rate          | IP20                  |                            |
| Light source     | COB module            |                            |
| Input Voltage    | AC220~240V            |                            |
| Dimming Type     | Non-Dimmable          |                            |
| Certificate      | CE,CCC                |                            |
| Cut Hole         | N/A                   |                            |

