


Item no. DD161-1515B9035

Series Name: AMMA Φ80 series Lens type (DD161)



■ Lighting Distribution Curve (cd/1000 lm)



■ Direct Horizontal Illuminance DD161-1515B9035

| φ | Illuminance Angle | Beam Angle | Vertical Illuminance(lx) |
|------|-------------------|------------|--------------------------|
| 15° | 16° | | 43960 |
| 260 | 1 | 20000 | 10990 |
| | | 10000 | 4880 |
| | | 5000 | 2750 |
| 520 | 2 | 2000 | 1760 |
| 780 | 3 | 1000 | 1220 |
| 1050 | m | 1 | 900 |
| | | 2 | 690 |

Luminous flux : 1340 lm

| | |
|------------------|---|
| Installation | Recessed mount |
| Type | High-efficiency Lens type small adjustable downlight |
| Fixture wattage | 14W |
| Beam angle | 16deg |
| Color Temp. | 3500K |
| CRI | Ra>90 |
| Luminous | 1338 lm |
| Body | Die-castaluminumalloy |
| Body finish | N/A |
| Trim finish | Black |
| Reflector finish | N/A |
| IP Rate | IP20 |
| Light source | COB module |
| Input Voltage | AC220~240V |
| Dimming Type | Non-Dimmable |
| Certificate | CE,CCC |
| Cut Hole | 80mm |

