


Item no. SD381-0815W9040-R-IK

Series Name: Clady versa R-G tracklight  
(In track) (SD381-R-IK)



■ Direct Horizontal Illuminance SD381-0815W9040-R-IK

| φ   | Illuminance Angle | Beam Angle | Vertical Illuminance(lx) |
|-----|-------------------|------------|--------------------------|
|     | 13°               | 14°        | 25290                    |
| 220 | 10000             |            | 6320                     |
|     | 5000              |            | 2810                     |
| 450 | 2000              |            | 1580                     |
|     | 1000              |            | 1010                     |
| 680 |                   |            | 700                      |
|     |                   |            | 520                      |
| 910 |                   |            | 400                      |

Luminous flux : 815 lm

|                  |                       |                            |
|------------------|-----------------------|----------------------------|
| Installation     | Track mount           |                            |
| Type             | Extra                 | high-efficiency tracklight |
| Fixture wattage  | 7.5W                  |                            |
| Beam angle       | 16deg                 |                            |
| Color Temp.      | 4000K                 |                            |
| CRI              | Ra>90                 |                            |
| Luminous         | 779 lm                |                            |
| Body             | Die-castaluminumalloy |                            |
| Body finish      | White                 |                            |
| Trim finish      | White                 |                            |
| Reflector finish | N/A                   |                            |
| IP Rate          | IP20                  |                            |
| Light source     | COB module            |                            |
| Input Voltage    | AC220~240V            |                            |
| Dimming Type     | Non-Dimmable          |                            |
| Certificate      | CE,CCC                |                            |
| Cut Hole         | N/A                   |                            |

