


Item no. SD381-1915B9040-R-IK

Series Name: Clady versa R-G tracklight
(In track) (SD381-R-IK)



■ Direct Horizontal Illuminance SD381-1915B9040-R-IK

| φ | Illuminance Angle | Beam Angle | Vertical Illuminance(Lx) |
|------|-------------------|------------|--------------------------|
| 1 | 15° | 16° | 43980 |
| 260 | | | 11000 |
| | | | 4890 |
| 520 | | | 2750 |
| | | | 1760 |
| 780 | | | 1220 |
| | | | 900 |
| 1050 | | | 690 |

Luminous flux : 1715 lm

| | | |
|------------------|-----------------------|----------------------------|
| Installation | Track mount | |
| Type | Extra | high-efficiency tracklight |
| Fixture wattage | 18.6W | |
| Beam angle | 16deg | |
| Color Temp. | 4000K | |
| CRI | Ra>90 | |
| Luminous | 1715 lm | |
| Body | Die-castaluminumalloy | |
| Body finish | Black | |
| Trim finish | Black | |
| Reflector finish | N/A | |
| IP Rate | IP20 | |
| Light source | COB module | |
| Input Voltage | AC220~240V | |
| Dimming Type | Non-Dimmable | |
| Certificate | CE,CCC | |
| Cut Hole | N/A | |

